



Terra Novo Inc., P.O. Box 81916, Bakersfield, CA 93380

www.earthguard.com



FULLY VEGETATED SLOPE AFTER TWO MONTHS OF HEAVY RAINFALL IN CASTLETON, VERMONT.

Castleton State College Project

Castleton State College is located amongst the beautiful rolling hills of Castleton, Vermont. The college initiated a project to revitalize its athletic facility. The General Contractor of the project,

Engleberth Construction, contacted Marty Montour of Trans-America Hydroseeding to stabilize and re-vegetate slopes on the project. Over the next couple of months, these slopes would experience

more than twenty inches of rainfall, making this one of the rainiest July's on record for the Northeast. EarthGuard Fiber Matrix not only successfully stabilized these slopes, but also produced thick vegetation.



JULY 10, 2009



AUGUST 11, 2009



OCTOBER 10, 2009

EarthGuard Fiber Matrix

www.earthguard.com

Erosion Control

Terra Novo, Inc., P.O. Box 81916, Bakersfield, CA

EarthGuard® is a soil stabilizing emulsion, specifically formulated to reduce erosion and sediment runoff. It is non-toxic, 100% biodegradable, and conforms to the **New York State Department of Transportation Qualified Products List under Class IV, Types A - C**. **EarthGuard® FM** is a one-step spray application, combining **EarthGuard®** and wood/cellulose fiber. It is applied as an aqueous slurry by itself or in combination with seed. **EarthGuard® FM** is chemically engineered to be effective at low rates while, absorbing the impact of raindrops, and providing immediate dust control, erosion control, and soil stabilization until permanent vegetation is established or construction has resumed. **EarthGuard® FM's** versatility allows it to be highly effective in many applications: erosion control, slope stabilization, dust abatement, landscape design, storm water runoff, fire burn rehabilitation, land development, landfill winterization and vegetation, roadway construction, and golf course construction.

For areas with greater than 20" of annual rainfall

Slope	5:1 or less	4:1	3:1 or greater
EarthGuard (gal/ac)	6	8	10
Mulch (lb./ac)	2,000	2,500	3,000

LONG TERM EROSION CONTROL OF PERMANENT SLOPES INCLUDING SEED

During the spring and summer months, follow the above charts for **EarthGuard®** and mulch rates. Add seed mixes as recommended to achieve long-term erosion control. This can be applied via a one-step hydroseeding process. However, some may prefer a two-step application (hydroseed and fertilizer first, and then **EarthGuard®** and mulch over the top).

WINTERIZATION

To winterize job sites or stockpiles, apply **EarthGuard FM** to achieve full-seasonal erosion control protection. This Winterization Best Management Practice (BMP) can be used to help your construction site comply with your local stormwater construction permit. Seeds, that may stay dormant until spring, may be added for growth in the spring.

EarthGuard (gal/ac)	10
Mulch (lb./ac)	3,000

FOR PARTIAL SEASON OR EXTENDED PROTECTION, CONTACT TERRA NOVO FOR RECOMMENDATIONS

STORM-BY-STORM PROTECTION

For temporary protection of slopes and flat areas that are still in progress, apply **EarthGuard** at 3-5 gallons per acre prior to a storm event with a water truck or spraying rig. After the rain has stopped and the ground is dry enough, proceed with grading.

APPLICATION & MIXING GUIDELINES

Spray all mixtures at a minimum rate of 3,000 gallons of water/acre (higher rates may be required) evenly over the area to be treated. Be careful not to spray too fast, creating puddles or run-off that may damage the soil structure before **EarthGuard** products can work. Application should be sprayed from multiple directions and angles to insure complete and proper coverage. Do not disturb treated areas after **EarthGuard** products are applied. Mulch manufacturers recommend all hydraulic applications using fiber mulch to have a 24-hour window without rain. Some situations with sandy-sandy loam soils, very little organic matter in the soil, poorly compacted slopes, heavy rainfall locations (over 30 inches per year), very intense rain storms (3-4 inches at a time), high wind exposure, etc. may require increasing the **EarthGuard** and/or mulch by 1.25-1.50 times. When SWPPPs, or other plans are being written, contact Terra Novo, Inc., or your local dealer for more specific rate recommendations.

EarthGuard can be stored for 6 months. Always thoroughly mix before using. Always close or seal containers after use. Store in a dry, insulated location to avoid moisture or freezing. Frozen product, once thawed, can and should be remixed.